



# Construction and Demolition Waste and Its Management Challenges in Iran: A Case Study in Tabriz City

Hassan Taghipour<sup>1,\*</sup>, Reza Taghizadeh Jazadani<sup>2</sup>, Reza Dehghanzadeh<sup>1</sup>, Mohamad Asghari Jafarabadi<sup>3</sup>, Mohsen Mir Mohammadi<sup>4</sup> and Mehdi Ghayebzadeh<sup>1</sup>

<sup>1</sup>Health and Environment Research Center, Department of Environmental Health Engineering, Faculty of Health, Tabriz University of Medical Sciences, Tabriz, Iran

<sup>2</sup>Student Research Committee, Department of Environmental Health Engineering, Tabriz University of Medical Sciences, Tabriz, Iran

<sup>3</sup>Department of Statistics and Epidemiology, Medical Education Research Center, Tabriz University of Medical Sciences, Tabriz, Iran

<sup>4</sup>Department of Environmental Engineering, Tehran University, Tehran, Iran

\*Corresponding author: Health and Environment Research Center, Department of Environmental Health Engineering, Faculty of Health, Tabriz University of Medical Sciences, Tabriz, Iran. Tel/Fax: +98-4133376228, Email: hteir@yahoo.com

Received 2017 September 28; Revised 2018 January 19; Accepted 2018 February 05.

## Abstract

**Background:** The management of construction and demolition (C&D) waste is among the fastest-growing concerns in Iran. Moreover, the basic prerequisites for the effective performance of every waste management program are the accessibility of adequate and precise data on characteristics and its current management condition.

**Objectives:** Estimating the amount of C&D waste in Tabriz metropolitan city (Iran) was one of the key aims of the current study. Another objective of this study was to evaluate of C&D waste handling and their final disposal.

**Methods:** The C&D waste generation rate was estimated according to the waste weight per area of construction and demolition in Tabriz. Then the C&D waste management condition was assessed using a checklist, visiting the disposal site, intervening authorities, and analyzing scientific databases.

**Results:** The amount of C&D waste generation rate in the Tabriz city was estimated to be in the range of 167034 to 848480 ton/year or 0.114 to 0.534 ton/year per capita and 2.267 ton/m<sup>2</sup> of demolition. In this area, like most other parts of the country, no scientific and systematic program was observed for source reduction (reduce, reuse, and recycle of the C&D waste). Due to the non-availability of any standard disposal site, all the C&D waste (except for some recycled items such as metals) were deposited at the nearest distance from the city in public lands, waterways, valleys, roadsides and so on.

**Conclusions:** According to the findings there is a great urgent need for applying specific practical policies, rules, and regulations for source reduction (reduce, reuse, and recycle (3R)) of C&D waste. Moreover, a central disposal site should be allocated to dispose of the remaining C&D waste according to the environmental and health considerations.

**Keywords:** Waste, Management, Environment, Iran

## 1. Background

Construction and demolition (C&D) waste is generated from the construction, renovation, and demolition of buildings, roads, bridges, land excavation or formation, and site of clearance or renovation of destroying communities due to natural or man-made disasters such as earthquake or war (1-3). A huge quantity of C&D waste in worldwide scale is the consequence of the rapid growth of population, urbanization, and development of the construction industry (4). For instance, in Lisbon (Portugal), the C&D generation rate was reported to be 0.60 ton/year per capita (5). The amount of C&D waste generation in the European Union was reported about 461 million tons annually (6). In South Korea, C&D waste equals 49.9% of the to-

tal generated waste with the production rate of 68 million ton/year (7). The generation rate of C&D waste in the UK estimated about 100 million tons per year (8). In Shanghai (China) with a population of about 24 million in 2012, about 13.7 million tons of C&D waste was produced (9). In 2003 in Tehran, the capital city of Iran, the generation rate of C&D waste was estimated at approximately 6.82 million tons per year (10). Moreover, in another study conducted in Shahroud city (Iran) in 2009 with a population of about 129000, an annual estimate of 0.219 million tons of C&D waste was reported (11).

Considering the C&D waste generation trend, it can be noted that the management and disposal of C&D waste become a serious environmental and health problem (2,

12). The most important C&D waste generation impacts are comprised of using a large number of land resources for waste landfilling/dumping, damaging the disposal site nearby by dangerous contamination, and wasting natural resources (9, 13).

In Iran, the management of C&D waste is among the fastest-growing concerns due to fast urbanization and population growth, and rapid development of the construction industry. In spite of that, the C&D waste management has not gained proper consideration. Consequently, designing a management plan for C&D waste is essential. On the other hands, the accessibility of adequate and precise data on characteristics and its current management conditions are among the basic prerequisites for the effective performance of every waste management program. The accessible data about C&D waste production rate in Iran is scarce. In addition, there are no accessible and precise data describing the real practice of managing and handling C&D waste.

## 2. Objectives

In this study, we firstly estimated the amount of C&D waste in Tabriz (Iran). Then we attempted to assess how C&D waste is handled and ultimately disposed of. In addition, we aimed to assess the existing policies on C&D waste management. Finally, some feasible suggestions about C&D waste management had been presented to enhance the present condition.

## 3. Methods

### 3.1. Study Area

Tabriz with an area of 324 km<sup>2</sup> and a population of 1,558 million people is the capital city of East Azerbaijan province and the fifth biggest city in Iran (14).

### 3.2. Estimating C&D Waste Generation Rate

Among the two main methodologies, which generally applied to estimate the C&D waste production rate, the second approach used for estimating C&D waste generation rate in this study (1, 15). In this method, C&D waste generation is determined according to the Equation 1, which is according to some measurements of the construction or demolition activity level in a district (by area of the structure, m<sup>2</sup>) and the average waste production per building area (tons/m<sup>2</sup>) (15).

$$W = CW + DW = CA \times G_c + DA \times G_d \quad (1)$$

where W is the total weight of building-related C&D waste (tons/year), CW and DW are the weight of construction waste and demolition waste (tons/year), respectively.

The CA is the area of buildings constructed or renovated, DA is the area of buildings demolished (m<sup>2</sup>/year), and G<sub>c</sub> and G<sub>d</sub> are the average waste generation per building area during construction and demolition activity (tons/m<sup>2</sup>), respectively (1, 15, 16).

In this study, the data of all the permits issued for construction of new buildings (CA) and demolition of old buildings (DA) were obtained from the Tabriz City Hall during 2003 to 2015 (m<sup>2</sup>/year). The area of permits issued for renovation was assumed as 10% of the permits issued for construction (m<sup>2</sup>/year). The average waste generation rate per building area during demolition (G<sub>d</sub>) activity was determined by weighing all the produced waste during the demolition of a randomly selected building (620 m<sup>2</sup> area and 3 floors) in Tabriz city (tons/m<sup>2</sup>). It should be added that the total waste volume was determined during weighing, which allowed for calculating the specific weight of the waste reported in kg/m<sup>3</sup>. The average waste generation rate per area of contraction (G<sub>c</sub>) activity was taken 2.27 kg/m<sup>2</sup> according to the previous study conducted by Mosavi and Hafezi Mogdas in 2010.

Non-building related waste (such as that from roads, bridges, and other structures) was included in this study. The amount of annual C&D waste (tons/year) was estimated for the past 13 years. Then a multilayer perceptron artificial neural network using the batch training method and gradient descent algorithm was used to predict the production of C&D waste in 2016 - 2025. The analyses were performed utilizing SPSS V. 17 statistical software (17).

### 3.3. Survey of the Current C&D Waste Management Condition

The data collection procedure used to assess current management conditions of C&D waste consisted of completing a checklist, visiting and observing the C&D waste disposal site, interviewing authorities, using scientific databases, and contacting the City Hall, local and national environmental protection agencies, and other organizations.

## 4. Results


### 4.1. Generation Rates of C&D Waste

Table 1 represents the summary of the result of determining the amount of waste generation in a demolished building. The generation rate of C&D waste for demolition and excavation and the total recyclable metals were determined to be 2.267 ton/m<sup>2</sup> and 0.05 ton/m<sup>2</sup> (50 kg/m<sup>2</sup>), respectively. The amount of area taken up by buildings constructed in Tabriz city (m<sup>2</sup>/year) during 2003 and 2015 is presented in Table 2. As revealed in Table 2, the amount of C&D waste was determined between 167034 and 848480


ton/year during 2003 - 2015. The trend of generation rate during the study period in Tabriz city was illustrated in Figure 1. As indicated, there is a sharp reduction in C&D waste generation in 2009 probably due to downswing in construction activity. Moreover, the annual generation rate of C&D waste per capita was obtained as 0.114 - 0.534 ton/year during the study period. The annual average amount and generation rate of C&D waste per capita were determined to be 591420 and 0.393 ton/year, respectively. Furthermore, it was estimated that an average of 12881 ton/year of metals was only being recycled by the demolition of buildings in Tabriz city. The waste generation rates for 2016 - 2025, were estimated to vary from 679349 to 742755 metric tons annually (Figure 2). Of course, as previously mentioned, the research team was not able to gather precise information on non-building-related waste, thus they were not included in this estimate. In this regard, if all C&D waste, including both building and non-building-related debris, were included in the dataset, the total estimated waste could be significantly more than the amount estimated by the current study. The comparison of the C&D waste generation rate in Tabriz city with those in other cities is presented in Table 3 (8). While the annual C&D waste generation rate was determined as 0.114 - 0.534 ton/year per capita (with an average of 0.393 ton/year) during the last 13 years in Tabriz city, it was reported to be between 0.107 and 1.18 ton/year per capita in both the developed and developing cities and countries. The variation in the generation rates (ton/year per capita) among different countries and cities can be due to various methods of construction and renovation, the quality and standards of primary building materials and rate and quality of developing processes, etc.

**Table 1.** The Summary of Result of Determining the Amount of Waste Generation in a Demolished Building

Items	Amount
Total area of demolished building, m <sup>2</sup>	620
Total weight of C&D waste, ton	1405.35
Weight of C&D waste without excavation for foundation, ton	904.72
C&D waste of excavation for foundation, ton	500.63
Weight of total metals item of C&D waste, ton	31
Total volume of C&D waste, m <sup>3</sup>	1146.40
C&D waste per area, ton/m <sup>2</sup>	2.267
C&D waste per area without excavation for foundation, ton/m <sup>2</sup>	1.459
C&D waste per area of excavation for foundation, ton/m <sup>2</sup>	0.808
Metals per area, ton/m <sup>2</sup>	0.05
Density of C&D waste, ton/m <sup>3</sup>	1.226



**Figure 1.** Trend of C&D waste generation in Tabriz city during 2003 - 2015



**Figure 2.** The estimated amount of generated C&D waste by artificial neural network estimates in Tabriz for the years 2016 to 2025

#### 4.2. Current C&D Waste Management Condition and Regulation in Tabriz City

Currently, there exists general legislation regarding waste management in Iran, which also uses to C&D waste. Based on clause 9 of the executive instruction comprised in that regulation, all C&D waste producers in cities and villages should pay attention to the instruction of separation, storage, and transportation of C&D waste. Meanwhile, no distinguished and clear regulation and instruction for separation, storage, transportation, and final disposal were presented. According to the municipality's regulation, C&D waste producers are only responsible for carrying generated waste out of cities or villages. In such a condition, after obtaining a demolition permit, the contractor collapses the building. During the period of de-

**Table 2.** Amount of Permission for Construction and Renovation (C&R) and Demolition and Consequence C&D Waste During 2003 Until 2015 in Tabriz City

Year	Construction Area, m <sup>2</sup> /y	Renovation Area, m <sup>2</sup> /y	Total C&R Area, m <sup>2</sup> /y	Generation Rate, ton/m <sup>2</sup>	C&R Waste, ton/y	Demolition Area, m <sup>2</sup> /y	Generation Rate, ton/m <sup>2</sup>	Demolition Waste, ton/y	Total C&D Waste, ton/y	Population of Tabriz (× 10 <sup>6</sup> )	C&D Waste, ton/y per capita
2003	3176226	317623	3493849		7931.04	275547		624665	632596	1.368	0.457
2004	2378155	237816	2615971		5938.25	206312		467709	473648	1.378	0.339
2005	1898620	189862	2088482		4740.85	164711		373400	378141	1.388	0.269
2006	2463875	246388	2710263		6152.30	213749		484568	490720	1.398	0.347
2007	2410484	241048	2651532		6018.98	209117		474068	480087	1.413	0.336
2008	3578355	357836	3936191		8935.15	310433		703752	712687	1.429	0.492
2009	838669	83867	922536	0.00227 (2.27 kg/m <sup>2</sup> )	2094.16	72757	2.267	164940	167034	1.445	0.114
2010	2879124	287912	3167036		7189.17	249773		566235	573424	1.461	0.388
2011	3672625	367263	4039888		9170.54	318611		722292	731462	1.495	0.483
2012	4151752	415175	4566927		10366.92	360177		816521	826888	1.532	0.533
2013	4260165	426017	4686182		10637.63	369582		837843	848480	1.570	0.534
2014	3747158	374716	4121874		9356.65	325077		736950	746307	1.648	0.447
2015	3148041	314804	3462845		7860.66	273102		619122	626983	1.689	0.367
Average	2969481	296948	3266429		7414.79	257611		584005	591420	-	0.393

**Table 3.** The Comparison of C&D Waste Generation Rate of the Studied City (Tabriz) with the Other Reported Researches

Estimated Study	Generation Rate, ton/y (× 10 <sup>6</sup> )	Population of Study Time (× 10 <sup>6</sup> )	Generation Rate, ton/y per capita
<b>This study (Tabriz city) between 2003 - 2015</b>	0.167- 0.848 (Ave = 0.591)	1.36 - 1.68	0.114 - 0.534 (Ave = 0.393)
<b>Tehran (capital city of Iran)</b>	6.82	7.5	0.909
<b>Shahroud (Iran)</b>	0.021	0.129	0.162
<b>United States (average of country) (16)</b>	170	290.1	0.586
<b>Lisbon (Portugal) (5)</b>	0.348	0.5	0.60
<b>European Union (6)</b>	461	490	0.94
<b>UK (8)</b>	100	63.7	1.56
<b>South Korea (7)</b>	68	50.22	1.35
<b>Shanghai city (China) (9)</b>	13.7	24	0.570
<b>Recife city (Brazil) (18)</b>	0.5	1.487	0.29

molition, recyclable materials are comprised of all metal items such as girders, pipes along with windows and doors and their frameworks (about 50 kg/m<sup>2</sup>), and a portion of woods for selling or sometimes reusing (breaks) in new building if possible. Then all remnant debris (more than about 95%) was loaded mechanically and sometimes manually as C&D waste to carrier trucks for transportation. Nevertheless, due to non-availability of any standard disposal site in the studied area, the carrier trucks generally unloaded the C&D waste at the nearest distance from the city in public lands, waterways, valleys, roadsides, even in pastures and conservation areas, and sometimes inside cities or nearby villages. Moreover, as there are no systematic controls over dumping C&D waste so that it can penalize whoever unloads C&D waste within the cities and villages' surroundings, no effort is made to reduce or recycle C&D waste in the area. It should be also explained that only little amount of C&D waste is sometimes used for land recla-

mation purposes. However, the method implemented for the C&D waste disposal in Tabriz city can create numerous environmental and health risks and even economic losses. The public health effects, environmental damages, and economic losses can include, but cannot exclude water and soil pollution, air pollution by particulate matter, creating unpleasant sights, making a shelter for rodent as a vector of some diseases, losing the property, and land worth and so on.

#### 4.3. Reviewing Appropriate Collection, Recycling and Disposal Programs, and Presenting a Waste Management Plan of C&D Waste for Tabriz (Iran)

Based on relevant scientific resources, the most important strategy and hierarchy for integrated management of the C&D waste is reducing source, reusing, recycling, and finally landfilling of the rest in a suitable disposal site (9, 19, 20). Reducing, reusing, and recycling are known as 3Rs of C&D waste management (2, 21). One of the best

ways for source reduction of the C&D waste is by increasing the lifetime of buildings and the quality of construction; consequently, the unnecessary destruction and demolition of buildings are decreased. Preventing the destruction of buildings due to economic reasons is another method of source reducing. The lifetime of buildings in Iran is 42 years, which in comparison to the average in industrialized countries is low (22). This can be due to the low quality of primary material used in construction, the low quality of construction processes, and even occasionally because of the policies of municipalities, which by issuing construction and destruction permissions, encourage citizens to destroy villa houses or one/two floor buildings and instead make multi-floor buildings and sometimes skyscrapers to gain greater profits. Therefore, for improving the C&D management condition, as the first step, the quality of primary material and standards of construction processes should be enhanced. The economic motivations for destroying buildings should be neutralized by applying suitable policies. Then particular and feasible policies, rules, and regulations should be approved and implemented to all levels of the C&D waste management. In the provision of sustainable feasible regulations, the experiences of other countries should be noticed. Moreover, a central final disposal site should be designated, designed, and operated for metropolitan cities such as Tabriz according to the environmental, health, and economic considerations. Ultimately, the responsible organizations should more strictly supervise the C&D waste collection, storage, recycling, and final disposal.

## 5. Discussion

The amount C&D waste in Tabriz city was estimated to be 167034 - 848480 and 0.114 - 0.534 ton/year per capita, which is more than that obtained in some other regions in Iran and in other countries. The C&D waste management condition in comparison to other cities in developed countries is not desirable. Currently, except for some recyclable materials such as metals, most of the C&D waste (averagely 591420 ton/year) are disposed in the suburb of Tabriz city. There is not any standard disposal site in the metropolitan city of Tabriz. Moreover, there is not any punishment or systematic controls for those who dump the C&D waste in the city's surrounding. In addition, no effort is made for reduction of C&D waste. Even though, the use of some bad policies such as application of non-standard materials in the construction of buildings, unsuitable supervision of construction processes, and sometimes issuance of permission by the city hall's officials for collapsing buildings for economical purposes causes an increase in the amount of C&D waste. Therefore, there is con-

siderable concern for C&D waste disposal regarding the environment, health, economy, and other aspects. As a result, a strong policy is recommended to be applied to source reduction, reuse, and recycle the C&D waste. Furthermore, a central final disposal site should be designed and operated for metropolitan cities e.g. Tabriz; meantime responsible organizations must also pay more attention to reducing C&D waste, reusing, recycling, and eventually, landfilling of the rest in suitable disposal sites.

## Footnotes

**Authors' Contribution:** Study design: Hassan Taghipour; manuscript preparation: Hassan Taghipour, Reza Taghizadeh Jazadani and Mohsen Mir Mohammadi; data collection: Reza Taghizadeh Jazadani, Reza Dehghanzadeh and Mehdi Ghayebzadeh; manuscript revision: Reza Dehghanzadeh; data analysis: Mohamad Asghari Jafarabadi.

**Conflict of Interests:** The authors declare they have no conflict of interest.

**Funding/Support:** The Research Deputy of Tabriz University of Medical Science funded this study (grant number: B.278).

## References

1. Cochran K, Townsend T, Reinhart D, Heck H. Estimation of regional building-related C&D debris generation and composition: Case study for Florida, US. *Waste Manag.* 2007;27(7):921-31. doi: [10.1016/j.wasman.2006.03.023](https://doi.org/10.1016/j.wasman.2006.03.023). [PubMed: [17258446](https://pubmed.ncbi.nlm.nih.gov/17258446/)].
2. Yuan HP, Shen LY, Hao JLL, Lu WS. A model for cost-benefit analysis of construction and demolition waste management throughout the waste chain. *Resourc Conserv Recycl.* 2011;55(6):604-12. doi: [10.1016/j.resconrec.2010.06.004](https://doi.org/10.1016/j.resconrec.2010.06.004).
3. Saca N, Dimache A, Radu LR, Iancu I. Leaching behavior of some demolition wastes. *J Mater Cycles Waste.* 2015;19(2):623-30. doi: [10.1007/s10163-015-0459-7](https://doi.org/10.1007/s10163-015-0459-7).
4. Ambros WM, Sampaio CH, Cazacliu BG, Miltzarek GL, Miranda LR. Usage of air jigging for multi-component separation of construction and demolition waste. *Waste Manag.* 2017;60(Suppl C):75-83. doi: [10.1016/j.wasman.2016.11.029](https://doi.org/10.1016/j.wasman.2016.11.029). [PubMed: [27908507](https://pubmed.ncbi.nlm.nih.gov/27908507/)].
5. De Melo AB, Gonçalves AF, Martins IM. Construction and demolition waste generation and management in Lisbon (Portugal). *Resourc Conserv Recycl.* 2011;55(12):1252-64. doi: [10.1016/j.resconrec.2011.06.010](https://doi.org/10.1016/j.resconrec.2011.06.010).
6. Jang YC, Townsend TG. Occurrence of organic pollutants in recovered soil fines from construction and demolition waste. *Waste Manag.* 2001;21(8):703-15. [PubMed: [11699628](https://pubmed.ncbi.nlm.nih.gov/11699628/)].
7. Somasundaram S, Jeon TW, Kang YY, Kim WI, Jeong SK, Kim YJ, et al. Characterization of wastes from construction and demolition sector. *Environ Monit Assess.* 2015;187(1):4200. doi: [10.1007/s10661-014-4200-0](https://doi.org/10.1007/s10661-014-4200-0). [PubMed: [25504191](https://pubmed.ncbi.nlm.nih.gov/25504191/)].
8. Department for Environment FRA - UK Government. *Statistics on waste statistical notice.* 2013, [updated 2015]. Available from: [https://www.gov.uk/government/uploads/system/uploads/attachment\\_data/file/487916/UK](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/487916/UK).



9. Yuan H, Shen L. Trend of the research on construction and demolition waste management. *Waste Manag.* 2011;**31**(4):670–9. doi: [10.1016/j.wasman.2010.10.030](https://doi.org/10.1016/j.wasman.2010.10.030). [PubMed: [21169008](https://pubmed.ncbi.nlm.nih.gov/21169008/)].
10. Omrani GA, Karbassi A, Monavari M, Usefi N. [Survey on collection, recycling and disposal condition of construction waste: Case study in Tehran]. *J Environ Sci Tech.* 2005;**7**(2):52–61. Persian.
11. Hafezi Mogdas N. Management of construction waste of Shahroud city according to environmental aspects. *7th Conference of Geology Engineering and Environment of Iran.* Shahroud Polytechnic University, Shahroud, Iran. 2010. Persian.
12. Esa MR, Halog A, Rigamonti L. Developing strategies for managing construction and demolition wastes in Malaysia based on the concept of circular economy. *J Mater Cycles Waste.* 2016;**19**(3):144–54. doi: [10.1007/s10163-016-0516-x](https://doi.org/10.1007/s10163-016-0516-x).
13. Esa MR, Halog A, Rigamonti L. Strategies for minimizing construction and demolition wastes in Malaysia. *Resourc Conserv Recycl.* 2017;**120**(Suppl C):219–29. doi: [10.1016/j.resconrec.2016.12.014](https://doi.org/10.1016/j.resconrec.2016.12.014).
14. *Statistical Center of Iran.* 2016. Available from: <https://www.amar.org.ir/english>.
15. Ding T, Xiao J. Estimation of building-related construction and demolition waste in Shanghai. *Waste Manag.* 2014;**34**(11):2327–34. doi: [10.1016/j.wasman.2014.07.029](https://doi.org/10.1016/j.wasman.2014.07.029). [PubMed: [25164857](https://pubmed.ncbi.nlm.nih.gov/25164857/)].
16. United States Environmental Protection Agency. *Estimating 2003 building-related construction and demolition materials amounts.* Office of Resource Conservation and Recovery Washington DC; 2009.
17. Fine TL. *Feedforward neural network methodology.* New York: Springer-Verlag; 1999.
18. Melo AD. *Construction and demolition waste management: Comparative study.* Brazil, Portugal, Lisbon; 2009.
19. Huang B, Wang X, Kua H, Geng Y, Bleischwitz R, Ren J. Construction and demolition waste management in China through the 3R principle. *Resourc Conserv Recycl.* 2018;**129**:36–44. doi: [10.1016/j.resconrec.2017.09.029](https://doi.org/10.1016/j.resconrec.2017.09.029).
20. Yang H, Xia J, Thompson JR, Flower RJ. Urban construction and demolition waste and landfill failure in Shenzhen, China. *Waste Manag.* 2017;**63**:393–6. doi: [10.1016/j.wasman.2017.01.026](https://doi.org/10.1016/j.wasman.2017.01.026). [PubMed: [28153408](https://pubmed.ncbi.nlm.nih.gov/28153408/)].
21. Patel S, Pansuria A, Shah V, Patel S. Construction and demolition waste recycling. *Int J Innov Res Sci Tech.* 2014;**1**(7):266–86.
22. Organization CoINS. *The life of Iranian buildings is the second time in other countries.* 2016. Available from: <http://donya-e-eqtesad.com/news/531164/>.